



钻床上专用倒角刀

钻床上专用倒角刀

倒角加工



型号 | BM4524T

产地 | 日本·Fujigen

产品描述

用途 钻床上使用倒角加工

特点 钻床专用！带断屑槽的高速钢刀片，切割锋利度超群。分别有30°、45°、60°的角度阵容

规格参数

型号	图	刃数	尺寸 (mm)								倒角加工能力 (刀片 型号) mm	
			φD	φDs	φd	φdn	L	ls	ln	角度	TM32GUR	TM32GSF
BM4524T	①	1	25.20	4.49	10	26	67	45	22	45°	φ5-φ24	φ5-φ21
BM4524TL	②	1	25.20	4.49	10	26	110	88	22	45°	φ5-φ24	φ5-φ21
BM4531T	③	1	33.06	11.57	12	33	75	50	25	45°	φ5-φ24	φ5-φ21
BM4538T	④	1	39.83	18.17	12	40	75	50	25	45°	φ5-φ24	φ5-φ21
BM4552T	⑤	1	53.91	32.17	13	54	80	55	25	45°	φ5-φ24	φ5-φ21
BM4566T	⑥	1	67.94	46.17	13	68	80	55	25	45°	φ5-φ24	φ5-φ21
BM4580T-JT6	⑦	1	81.96	60.17	-	82	40	-	-	45°	φ5-φ24	φ5-φ21
BM4594T-JT6	⑦	1	95.96	74.17	-	96	40	-	-	45°	φ5-φ24	φ5-φ21
BM45100T-JT6	⑦	1	101.96	80.16	-	101	40	-	-	45°	φ5-φ24	φ5-φ21
BM45108T-JT6	⑦	1	109.96	88.17	-	110	40	-	-	45°	φ5-φ24	φ5-φ21
BM3029T	⑧	1	30.2	5.52	10	30	74	45	29	30°	φ5-φ24	φ5-φ21
BM3047T	⑨	1	47.39	21	12	47.5	75	50	25	30°	φ5-φ24	φ5-φ21
BM6021T	⑩	1	21.77	6.60	10	23	69	45	24	60°	φ5-φ24	φ5-φ21
BM6030T		1	30.38	15	12	30.4	75	50	25	60°	φ5-φ24	φ5-φ21

规格参数

材质	进刀量 (fz)	切削速度 (m/min)	旋转数 (r.p.m.)	切削液	推荐刀片
普通钢	-	5-25	-	-	TM32GUR HSS、 TM32GSR HSS
合金钢	-	5-25	-	-	TM32GUR HSS TiAlN、 TM32GSR HSS TiAlN
淬火钢HRC~45	-	5-25	-	-	TM32GUR HSS TiAlN、 TM32GSR HSS AC16N
淬火钢HRC45~65	-	-	-	-	-
不锈钢	-	5-25	-	-	TM32GUR HSS TiAlN、 TM32GSR HSS AC16N
铸铁	-	5-25	-	-	TM32GUR、 TM32GSR
树脂	-	10-30	-	-	TM32GUR HSS、 TM32GSR HSS
铝合金	-	10-30	-	-	TM32GUR HSS、 TM32GSR HSS
钛合金镍合金	-	-	-	-	-

规格参数

型号	主轴旋转数 (r.p.m.)				
	TM32GUR HSS	TM32GUR HSS TiAlN	TM32GSR HSS	TM32GSR HSS TiAlN	TM32GSR HSS AC16N
BM4524T	160-320	200-400	160-320	200-400	200-400
BM4524TL	160-320	200-400	160-320	200-400	200-400
BM4531T	130-280	150-350	130-280	150-350	150-350
BM4538T	130-280	150-350	130-280	150-350	150-350
BM4552T	80-120	100-150	80-120	100-150	100-150
BM4566T	40-80	50-100	40-80	50-100	50-100
BM4580T-JT6	20-50	20-50	20-50	20-50	20-50
BM4594T-JT6	20-50	20-50	20-50	20-50	20-50
BM45100T-JT6	20-50	20-50	20-50	20-50	20-50
BM45108T-JT6	20-50	20-50	20-50	20-50	20-50
BM3029T	160-320	200-400	160-320	200-400	200-400
BM3047T	130-280	150-350	130-280	150-350	150-350
BM6021T	160-320	200-400	160-320	200-400	200-400
BM6030T	130-280	150-350	130-280	150-350	150-350

规格参数

图片	型号	材质类型	使用角数	标准包装
	TM32GUR	HSS	2	3pcs/盒
		HSS TiAlN		
	TM32GSR	HSS	6	
		HSS TiAlN		
		AC16N		