

针盘式扭力扳手



型号 | TOK-G

产地 | 日本·Kanon

产品描述

特点

刻度表盘易于阅读以进行检查
表盘侧面附有坚固的防护罩
椭圆形设计与舒适的橡胶握把减少了压力
左右通用、检查均可使用
置针方便拧紧查看峰值
精度保证在 $\pm 3\%$ 以内

用途

适用于拧紧和检查先前拧紧螺丝的扭矩
也适合螺栓和螺母的松动和断裂测试

规格参数

型号	调整范围	最小读值	型号	调整范围	最小读值	四角头	全长	尺寸 (mm)						
公制	kgf · cm/kgf · m	牛顿		N · m			mm	A	B	C	D	E	F	G
60TOK-G	6-60kgf · cm	1kgf · cm	N6TOK-G	0.6-6	0.1	6.35 (1/4")	260	35	38.5	7.5	58	90	37	21.5
120TOK-G	10-120"	2"	N12TOK-G	1-12	0.2		260	35	38.5	7.5	58	90	37	21.5
300TOK-G	50-300"	5"	N30TOK-G	5-30	0.5	9.35 (3/8")	323	35	43	11	60	90	37	21.5
500TOK-G	50-500"	5"	N50TOK-G	5-50	0.5		323	35	43	11	60	90	37	21.5
700TOK-G	100-700"	10"	N70TOK-G	10-70	1		323	35	43	11	60	90	37	21.5
1400TOK-G	200-1400"	20"	N140TO K-G	20-140	2	12.7 (1/2")	463	39	49	14	65	90	41	22.5
2000TOK-G	200-2000"	20"	N200TO K-G	20-200	2		463	39	49	14	65	90	41	22.5
3000TOK-G	3-30kgf · m	0.5kgf · m	N300TO K-G	30-300	5	19.05 (3/4")	652	41	55	20	77	90	φ30	
4200TOK-G	4-42"	1"	N420TO K-G	40-420	10		955	48	60	20	77	90	φ34	
5500TOK-G	5-55"	1"	N550TO K-G	50-550	10		1110	50	60	20	80	90	φ38	φ30
7000TOK-G	7-70"	1"	N700TO K-G	70-700	10	25.4 (1")	1280	54	64	20	85	90	φ43	φ32
8500TOK-G	10-85"	1"	N850TO K-G	100-850	10		1384	58	72	27	93	90	φ45	φ34
10000TO K-G	10-100"	2"	N1000TO K-G	100-1000	20		1484	66	74	27	94	90	φ51	φ40
14000TO K-G	20-140"	2"	N1400TO K-G	200-1400	20		1696	66	74	27	94	90	φ51	φ40